



Cordless Grass Shear DUM111 110 mm



Smooth grass cutting and hedge trimming



110mm cutting width for optimum performance



Tool-less blade change system

- Grass shear blade can be removed / installed without tool.
- Hedge trimmer blade can be removed / installed by using a coin to loosen / tighten two screws.

Powered by 18V slide Li-ion battery



Accessories

Hedge trimmer blade

Part No. 191N24-2
200mm(7-7/8")



Chip receiver

Part No. 198401-5



Blade cover set

Part No. 195274-7



Blade cover
Part No. 458342-0



Storage case
Part No. 452198-3

Long handle attachment

Part No. 198486-1




Grass shear blade

Part No. 191N23-4
110mm



Grass receiver set

Part No. 191N25-0



Grass receiver 110
Part No. 454880-0



Storage case
Part No. 452198-3



Blade cover 110
Part No. 413885-9

Long handle attachment with wheel

Enables to use the machine comfortably in a standing posture.

- 5 stage angle adjustment allows for grip height adjustment according to user's height.
- Lock-off button operable from both left and right side



Charging Time

| | DC18RC | DC18SD |
|---------------|--------|---------|
| BL1815N 1.5Ah | 15 min | 30 min |
| BL1820B 2.0Ah | 24 min | 45 min |
| BL1830B 3.0Ah | 22 min | 60 min |
| BL1840B 4.0Ah | 36 min | 90 min |
| BL1850B 5.0Ah | 45 min | 110 min |
| BL1860B 6.0Ah | 55 min | 130 min |

Cordless Grass Shear

DUM111 110 mm

| | |
|---------------------------------|---|
| Cutting Width | Grass Shear Blade: 110 mm (4-5/16") Hedge Trimmer Blade: 200 mm (7-7/8") |
| Depth Adjustment | 15, 20, 25 mm (9/16, 13/16, 1") |
| Strokes Per Minute (SPM) | 2,500 |
| Continuous Use (min.) | w/ BL1850B / BL1815N: 220 / 67 |
| Sound Pressure Level | 70 dB(A) |
| Vibration Level | 2.5 m/s ² or less |
| Dimensions (L x W x H) | w/o Battery: 300 x 120 x 130 mm (11-3/4 x 4-3/4 x 5-1/8") w/ BL1815N / BL1820B: 330 x 120 x 130 mm (13 x 4-3/4 x 5-1/8") |
| Net weight | 1.4 - 1.8 kg (3.1 - 4.0 lbs.) |
| Standard Equipment | :Blade Cover, Battery, Charger |

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202102