



# Battery Powered Lawn Mower LM001C 534 mm (21") Self-Propelled



## Long continuous operation

Mowing area (push-drive mode)

PDC1200

**6,900 m<sup>2</sup>**

---

PDC01 (BL1860B x4)

**2,300 m<sup>2</sup>**

### PDC1200

Powered by 36V-40Vmax built-in battery

### PDC01

Powered by up to four 18V LXT batteries



Using Makita Portable Power Pack





### Side discharge



with side discharge mouth

### Cutting height is adjustable by one handle



### Control panel

- 3 cutting modes
  - Normal mode
  - Soft no-load mode
  - Noise reduction mode
- Main switch



### Self-propelled type

Self-propelled speed: 2.5-5.0 km/h



### Grass level indicator



### BL MOTOR



### PDC01 (Option)



### PDC1200 (Option)



### XPT

IPX4-rated water-resistance



### Higher mowing performance



The blade is designed so that it tilts towards the front side of the mower when attached, preventing double-cutting for reduced current consumption.

Optimum blade design for less rotational speed reduction of the blade

### Steel Deck

## Portable Power Pack

### Portable Power Pack

#### PDC1200

Powered by 36V-40Vmax built-in battery



Charger DC4001



#### PDC01

Powered by up to four 18V LXT batteries



## Battery Powered Line-up

#### Blower

#### UB001C



#### Grass Trimmer

#### UR101C UR201C UR202C



#### Lawn mower

#### LM001C



## Accessories

### Blade

Size: 530mm  
Part No. 191D52-7



### Swing back blade

Swing back blade 530 cpl. set  
Size: 530mm  
Part No. 191D50-1



Swing back blade 530 set (4 pcs)  
Part No. 191D48-8

## Battery Powered Lawn Mower

### LM001C 534 mm (21") Self-Propelled

- Brake
- Electronic 2-Speed
- Constant Speed
- Soft Start

#### Standard Equipment:

Blade, Mulch Plug, Side Discharge Mouth, Box Wrench, Rod

<b>Cutting Width</b>	534 mm (21")
<b>Cutting Height</b>	20 - 100 mm (13/16 - 3-15/16")
<b>Grass Box Capacity</b>	70 L
<b>No Load Speed (RPM)</b>	2,300 - 2,800
<b>Propelling Speed</b>	2.5 - 5.0 km/h
<b>Actual Mowing Area</b>	w/ PDC01 (BL1860B X4), Self-Propelled: 1,700 m <sup>2</sup> w/ PDC01 (BL1860B X4), push-drive: 2,300 m <sup>2</sup> w/ PDC1200, Self-Propelled: 5,100 m <sup>2</sup> w/ PDC1200, push-drive: 6,900 m <sup>2</sup>
<b>Continuous Use (min.)</b>	w/ PDC01 (BL1860B X4), Self-Propelled: 40 w/ PDC01 (BL1860B X4), push-drive: 50 w/ PDC1200, Self-Propelled: 120 w/ PDC1200, push-drive: 150
<b>Sound Pressure Level</b>	80.0 dB(A)
<b>Sound Power Level</b>	91.2 dB(A)
<b>Vibration Level</b>	2.5 m/s <sup>2</sup> or less
<b>Dimensions (L x W x H)</b>	1,630 - 1,715 x 590 x 990 - 1,095 mm (64 - 67-1/2 x 23-1/4 x 39 - 43")
<b>Net weight</b>	42.1 - 49.5 kg (92.8 - 109.1 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202103