



Job Site Radio
DMR112 7.2-18V / AC



Compatible with Makita Li-ion batteries

excluding G-batteries

Capable of receiving

DAB · DAB+



Compatible with
7.2V, 10.8V, 12Vmax, 14.4V, 18V Li-ion batteries





DAB · DAB+

equipped with Bluetooth class 2** to wirelessly play music from a mobile device.
 **With a range of 10m (33ft); up to 30m (100ft) in good radio conditions

• A mobile device can be stably placed on the top.

Foldable antenna



Carry handle

- Swivels 90 degrees
- Features soft grip



Dust and shower-proof construction: IP64

For use in outdoor applications or harsh environments

Elastomer bumpers

protect against rough handling with falling impact strength of 1.0m.

Front metal pipe

Large Ø 89mm speaker

AUX-IN jack

used as a stereo speaker by connecting to external audio source with a commercial connecting cable.

AC adapter jack

USB output port

- allows for charging a mobile device.
- Type A USB socket for DC5V/ 1.0A USB output



Dual Power Sources

Runs on AC adapter or Makita rechargeable Li-ion batteries.

Continuous run time (approx): hour

7.2V LITHIUM-ION	1.5Ah BL0715	7.5	LXT	1.5Ah BL1415N	7.0
				3.0Ah BL1430B	12
				4.0Ah BL1440	19
10.8V LITHIUM-ION	1.3Ah BL1013	7.0	14.4V LITHIUM-ION	5.0Ah BL1450	23
				6.0Ah BL1460B	25
				1.5Ah BL1815N	7.5
CXT	1.5Ah BL1016	8.5	LXT	2.0Ah BL1820B	10
				3.0Ah BL1830B	14
12Vmax LITHIUM-ION	2.0Ah BL1020B	11	18V LITHIUM-ION	4.0Ah BL1840B	20
				5.0Ah BL1850B	26
	4.0Ah BL1040B	21		6.0Ah BL1860B	31

On a single full battery charge



- 14.4V LITHIUM-ION** / **18V LITHIUM-ION**
 BL1415N / BL1415 / BL1430B / BL1430 / BL1440 / BL1450 / BL1460B / BL1815N / BL1820B / BL1830B / BL1840B / BL1850B / BL1860B
- 7.2V LITHIUM-ION** / **10.8V LITHIUM-ION**
 BL0715, BL1013
- 12Vmax LITHIUM-ION**
 BL1016, BL1021B, BL1041B

Job Site Radio

DMR12 7.2-18V / AC

Frequency Band	FM / DAB / DAB+: 87.5 - 108 MHz / 174.928 - 239.200 MHz / 174.928 - 239.200 MHz
Speaker Size	Woofer: Ø89 mm x 2
Max Output	18 V: 4.9 W x2, 14.4 V: 3 W x2, 12V max: 1.7 W x2, 7.2 V: 0.6 W x2
Bluetooth	Version: 4.0 Profile: A2DP / SCMS-T Supported Codec: SBC / AAC Max Transmission Range (Optimum): 10 m (33 ft) Max Transmission Range (Possible): 30 m (98 ft) Transmission Power Class: 2 Compatible Bluetooth Profile: A2DP
Dimensions (L x W x H)	w/ Handle in Retracted Position: 282x163x294 mm (11-1/8"x6-3/8"x11-5/8") w/ Handle in Upright Position: 262x163x431 mm (10-3/8"x6-3/8"x17")
Net weight	4.3 - 4.9 kg (9.5 - 10.9 lbs.)
	Standard Equipment : AC Adaptor

The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201811