



## Cordless Grass Trimmer DUR184L

Satisfy Professional's Needs



**BL**  
MOTOR

**Comfortable short telescopic pipe,  
providing easy handling in tight  
spaces.**



# Better maneuverability regardless of user's size by telescopic pipe



## Short pipe for better maneuverability

Allows to hold the machine in a comfortable posture and provides easy handling even in tight places, because this pipe is:

- Shorter than the current model.
- Slightly curved down.
- Equipped with main grip set at an ergonomic angle.

## Telescopic pipe

adjustable in length from 1,534mm (60-1/2") to 1,634mm (64-1/2")

100mm




## Ergonomic loop handle for added maneuverability

- Provides easy handling especially on level ground.
- Toolless removal/installation
- Installation position is adjustable to any desired position without tool.

## Smaller protector for better view of cutting area

Compact protector for nylon cutting head provides better view of the blade tips, without losing the performance for prevention of scattering of grass clippings.



## High / Low 2-speed selection

- 6,000 / 5,000 rpm
- Optimum speed setting for Nylon cutting head
- Run time can be extended by lowering the number of rotations according to weed type and location.
- Speed mode can be changed by simply pushing a button on the handle.
- Speed setting memory records the final setting speed.

## Reverse switch for easy removal of grass clippings from the cutting tool

Grass clippings can be removed by slow reverse rotation of the cutting tool.



## High Performance with Brushless DC Motor



## Electric brake

stops the rotation of the cutting tool gently but fast, allowing user to quickly resume operation.



## 18V Li-ion battery

with Battery fuel gauge

- BL1860B: 6.0Ah
- BL1850B: 5.0Ah
- BL1840B: 4.0Ah
- BL1830B: 3.0Ah



- BL1820B: 2.0Ah



- BL1815N: 1.5Ah (without Battery fuel gauge)

BL1815N

## Fast Charger

DC18RC



## Charger

DC18SD



## Cordless Grass Trimmer

## DUR184L

- Brake
- Reversing
- Electronic 2-Speed
- Constant Speed
- Sort Start

No Load Speed (rpm)	High / Low: 6,000 / 5,000
Cutting Width	Trimmer Head: 300 mm (11-3/4")
Spindle Size	M8 x 1.25 RH
Sound Pressure Level	77 dB(A)
Sound Power Level	89 dB(A)
Vibration Level	Front / Rear: 2.5 / 2.5 m/s <sup>2</sup> or less
Vibration K factor	Front / Rear: 1.5 / 1.5 m/s <sup>2</sup>
Dimensions (L x W x H)	1,534-1,634 x 258 x 417 mm (60-1/2" - 64-1/2" x 10-1/8" x 16-3/8")
Max output	250W
Max Run Time (min)	With BL1850B: 80
Net weight	BL1850B: 3.6 kg (7.9 lbs) BL1815N: 3.3 kg (7.3 lbs)

Standard Equipment : Safety Goggles, Single harness, Nylon cutting head, Accessory Bag, Charger, Battery, Hex wrench x2, Battery cover

weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201602