

Makita

Cordless Inflator
MP100D

Safety Professional's Needs

CXT

**From daily maintenance to
outdoor activity.**



12V^{max}
LITHIUM-ION

Max air pressure

830 [121PSI]
kPa

Air Discharge Amount

10 [200kPa]
L/min

Net weight

1.2 [with BL1016]
kg

10 L/min
[2000Pa]

Net weight
1.2 kg
[with BL 10142]



Blows Up Air in the Tires of Cars/Bikes

Max air pressure **830** ^[121PSI] **kPa**



LED job Light
for easy operation at dark places.



Digital pressure gauge provides high visibility with backlight.

- Comes with valve adapters



None can be stored



Valve adjusters

	Car / Motorcycle	Bicycle	Road bike	Ball	Beach ball / For Swim ring
Wire shape					
Adapter (Needed equipment)	American 	British 	French 	For Balls 	For Swim ring/ Beach balls 
Maximum air pressure: kPa	(approx) 250	(approx) 300	(approx) 700	100 and under	50 and under
Discharge amount: L/ min (at target pressure)	10	9	4	11	11.5
a single full battery charge count (with 10,000 psi)	Car tires (215/60R16) 2	Bicycle tires (1.9in/48cm) 46	Road bike tires (700x23c) 20	Soccer balls (Size 5) 63	Beach balls (4in/10cm) 54

Cordless Inflator
MP1000

	Built-in Job Light	Max. air Pressure	400 kPa (120 PSI)
		Air Discharge Amount	200 kPa (12 PSI)
	Camping Case	Dimensions (L x W x H)	200 x 100 x 100 mm (7.9 x 3.9 x 3.9 in.)
			200 x 100 x 100 mm (7.9 x 3.9 x 3.9 in.)
			200 x 100 x 100 mm (7.9 x 3.9 x 3.9 in.)
			200 x 100 x 100 mm (7.9 x 3.9 x 3.9 in.)
		Net weight	0.2 kg (0.4 lb)

Standard Equipment:
British Adapter, French Adapter, Rail Adapter,
Custom Wire Adapter, Buffers, (Thumper)

The weight may differ depending on the attachment(s) including the battery cartridge. The lightest and heaviest combinations, according to EN60950-1, are shown in the table.

None of standard equipment and qualifications may vary by country or area.

Makita Corporation

3-15-8 Sumiyoshi-cho, Arjo, Aichi, 465-8522 Japan

© 2004 Blackwell Publishing Ltd *Journal of Internal Medicine* 255: 105–112